

Mosaic™

data sockets Cat. 5e, Cat. 6 and 10 GIGA - tool less



742 44



742 85



742 80



742 84

Certified as conforming to standards ISO 11801 - ed.2.0, EN 50173-1 and EIA/TIA 568

Tool less fast connection sockets

Contacts marked with dual colour code 568 A and B and numbers

Connectors with insulation displacement contacts

Can be rewired in the event of an error

Multidirectional cable entry enables installation in shallow trunking, 34 mm for UTP and FTP connectors, 50 mm for STP

Take RJ 45, RJ 12 or RJ 11 plugs with no distortion of the contacts

Pack	Cat.Nos		RJ 45 - tool less system		
			10 GIGA		
			STP - metal shielding		
			The shielding is easy to fit, once the socket is connected		
			9 contacts, metal shielding, 1 RJ 45		
10			1 module		
10			2 modules		
			Cat. 6 and cat. 5e UTP		
10	Cat. 5e	Cat. 6	8 contacts	Number of modules	22.5 x 45 mm
10	742 85	742 80	8 contacts	1	
10	742 86	742 81	8 contacts	2	
			Cat. 6 and cat. 5e FTP		
10	742 88	742 90	9 contacts	1	
10	742 89	742 91	9 contacts	2	
10		742 92	9 contacts - installation at 90° possible on columns and mini-columns	2	
			Cat. 6 and cat. 5e STP - metal shielding		
			The shielding is easy to fit once the socket is connected		
10	742 83	742 93	1 shielded	1	
10	742 84	742 94	1 shielded	2	
10		742 87	1 Zamak shielded	2	
10		742 95	2 RJ - 2 Zamak modules	2	

Pack	Cat.Nos		Rear pluggable RJ 45 sockets		
			For use with zone distribution boxes		
			Connection to boxes via RJ 45 - RJ 45 dedicated cords (p. 795)		
			Used to create Cat. 6 and Cat 5e links in accordance with standards ISO 11801 ed.2.0, EN 50173-1 and EIA/TIA 568 B2		
			Multi-directional cable entry		
			Can be installed in all supports minimum depth 40 mm		
			Cat. 6		
10			UTP	Number of modules	22.5 x 45 mm
10			FTP	2	
			Cat. 5e		
10			UTP	2	
10			FTP	2	

Mosaic™

data sockets - 110 connect



742 13



6339 80



6339 81



742 96



332 60

Transmission of voice, data and image

Enables RJ 45 Cat. 5e and Cat. 6 installation conforming to ISO 11801 - 2d

Fast tool connection insulation for displacement terminals

IDC lateral connection

Double colour code EIA 568 A and B

Transparent label holder

Pack	Cat.Nos		RJ 45 - 110 connect		
			UTP (without screen)		
10	Cat. 5e	Cat. 6	8 contacts	Number of modules	17.5 mm
10	742 13	6339 80	8 contacts	1	
10	742 14	6339 81	8 contacts	2	
			FTP (with screen)		
10	Cat. 5e		9 contacts	1	
10	742 63		9 contacts	2	
10	742 64		9 contacts	2	
			STP shielded		
			EMC shielding cover		
10	742 96		9 contacts	1	
10	742 97		9 contacts	2	

Pack	Cat.Nos	Impact tool 110 connect	
		For connecting sockets and patch panels fitted with self-stripping terminals, type 110 ensures the right amount of pressure exerted for size of wire cut	
1	332 60	Cabling tool 110 supplied with blade	

Pack	Cat.Nos	Accessories		
		Coloured label holders		
		5 red and 5 green		Number of modules
1	747 89	5 red and 5 green		22.5 x 45 mm
1	747 88			1
				2