

# over floor trunking



300 92



300 93



328 00




893 07

For creating a link between trunking, column, mini-column, floor units or protecting cables on passageways  
Supplied with cover


## Over floor trunking 50 x 12 mm

Pack	Cat.Nos	
54 <sup>(1)</sup>	300 92	<b>Trunking</b> Length 2 m, supplied with cover 3 compartments Capacity 1: max. Ø9 mm Capacity 2: max. Ø6 mm IP 40 - IK 07 RAL 7030  <b>Accessories</b>
10	300 12	Cover joint
10	300 11	Flat angle
4	300 13	Junction box




## Over floor trunking 92 x 20 mm

Pack	Cat.Nos	
20 <sup>(1)</sup>	328 00	<b>Trunking</b> Length 2 m, supplied with cover 4 compartments Equipped with 2 adhesive strips for better floor fixing Capacity 1: max. Ø14.5 mm Capacity 2: max. Ø9.5 mm IP 40 - IK 08 RAL 7016  <b>Accessories</b>
10	328 07	End cap
10	328 03	Cover joint
5	328 02	Flat angle
1	328 05	Connection for mini-trunking installed as 60 x 20 or 75 x 20 skirting trunking
5	328 01	Distribution box For spurs in 4 directions with separation of currents



## Over floor trunking 75 x 18 mm

Pack	Cat.Nos	
36 <sup>(1)</sup>	300 93	<b>Trunking</b> Length 2 m, supplied with cover 3 compartments Capacity 1: max. Ø14 mm Capacity 2: max. Ø11 mm IP 40 - IK 07 RAL 7030  <b>Accessories</b>
10	300 19	Cover joint
10	300 18	Flat angle
4	300 13	Junction box




## Junction for trunkings

		To be used with Cat.No 328 00
5	107 70 + 106 90	For cover 40 mm
5	107 71 + 106 90	For cover 65 mm
5	107 72 + 106 90	For cover 85 mm
5	107 74 + 106 90	For cover 130 mm



## Floor access box

1	893 07	For wiring in raised floors (25 to 55 mm) IP 20 - IK 08 Base made of 2 parts: aluminium and polyester with neoprene seal 3 x Ø20 mm outlets Cut-out dimensions: Ø127 mm Frame dimensions: Ø144 mm Flush depth: 60 mm
---	--------	---



**DLP columns**

see p. 740